

Fonts and FreeBSD

A Tutorial

Dave Bodenstab <imdave@synet.net>

Revision: 52891

FreeBSD is a registered trademark of the FreeBSD Foundation.

Adobe, Acrobat, Acrobat Reader, Flash and PostScript are either registered trademarks or trademarks of Adobe Systems Incorporated in the United States and/or other countries.

Apple, AirPort, FireWire, iMac, iPhone, iPad, Mac, Macintosh, Mac OS, Quicktime, and TrueType are trademarks of Apple Inc., registered in the U.S. and other countries.

Linux is a registered trademark of Linus Torvalds.

Microsoft, IntelliMouse, MS-DOS, Outlook, Windows, Windows Media and Windows NT are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

Motif, OSF/1, and UNIX are registered trademarks and IT DialTone and The Open Group are trademarks of The Open Group in the United States and other countries.

Many of the designations used by manufacturers and sellers to distinguish their products are claimed as trademarks. Where those designations appear in this document, and the FreeBSD Project was aware of the trademark claim, the designations have been followed by the “™” or the “®” symbol.

2019-03-23 04:50:01 by bcr.

Abstract

This document contains a description of the various font files that may be used with FreeBSD and the syscons driver, X11, Ghostscript and Groff. Cookbook examples are provided for switching the syscons display to 80x60 mode, and for using type 1 fonts with the above application programs.

Table of Contents

1. Introduction	2
2. Basic Terminology	2
3. What Font Formats Can I Use?	2
4. Setting a Virtual Console to 80x60 Line Mode	3
5. Using Type 1 Fonts with X11	3
6. Using Type 1 Fonts with Ghostscript	5
7. Using Type 1 Fonts with Groff	6
8. Converting TrueType Fonts to a groff/PostScript Format For groff	7
9. Can TrueType Fonts be Used with Other Programs?	9
10. Where Can Additional Fonts be Obtained?	9
11. Additional Questions	9

1. Introduction

There are many sources of fonts available, and one might ask how they might be used with FreeBSD. The answer can be found by carefully searching the documentation for the component that one would like to use. This is very time consuming, so this tutorial is an attempt to provide a shortcut for others who might be interested.

2. Basic Terminology

There are many different font formats and associated font file suffixes. A few that will be addressed here are:

`.pfa`, `.pfb`

PostScript® type 1 fonts. The `.pfa` is the Ascii form and `.pfb` the Binary form.

`.afm`

The font metrics associated with a type 1 font.

`.pfm`

The printer font metrics associated with a type 1 font.

`.ttf`

A TrueType® font

`.fot`

An indirect reference to a TrueType font (not an actual font)

`.fon`, `.fnt`

Bitmapped screen fonts

The `.fot` is used by Windows® as sort of a symbolic link to the actual TrueType® font (`.ttf`) file. The `.fon` font files are also used by Windows. I know of no way to use this font format with FreeBSD.

3. What Font Formats Can I Use?

Which font file format is useful depends on the application being used. FreeBSD by itself uses no fonts. Application programs and/or drivers may make use of the font files. Here is a small cross reference of application/driver to the font type suffixes:

Driver

`vt`

`.hex`

`syscons`

`.fnt`

Application

Ghostscript

`.pfa`, `.pfb`, `.ttf`

X11

`.pfa`, `.pfb`

Groff

`.pfa`, `.afm`

Povray

`.ttf`

Spacing

proportional or monospaced. *Proportional* is used since *isFixedPitch* is false.

All of these names are arbitrary, but one should strive to be compatible with the existing conventions. A font is referenced by name with possible wild cards by an X11 program, so the name chosen should make some sense. One might begin by simply using

```
...-normal-r-normal-...-p-...
```

as the name, and then use [xfontsel\(1\)](#) to examine it and adjust the name based on the appearance of the font.

So, to complete our example:

```
Make the font accessible to X11
% cd /usr/X11R6/lib/X11/fonts/Type1
% ln -s /usr/local/share/fonts/type1/showboat.pfb .

Edit fonts.dir and fonts.scale, adding the line describing the font
and incrementing the number of fonts which is found on the first line.
% ex fonts.dir
:lp
25
:lc
26
.
:$a
showboat.pfb -type1-showboat-medium-r-normal-decorative-0-0-0-p-0-iso8859-1
.
:wq

fonts.scale seems to be identical to fonts.dir...
% cp fonts.dir fonts.scale

Tell X11 that things have changed
% xset fp rehash

Examine the new font
% xfontsel -pattern -type1-*
```

References: [xfontsel\(1\)](#), [xset\(1\)](#), *The X Windows System in a Nutshell*, O'Reilly & Associates.

6. Using Type 1 Fonts with Ghostscript

Ghostscript references a font via its Fontmap. This must be modified in a similar way to the X11 `fonts.dir`. Ghostscript can use either the `.pfa` or the `.pfb` format fonts. Using the font from the previous example, here is how to use it with Ghostscript:

```
Put the font in Ghostscript's font directory
% cd /usr/local/share/ghostscript/fonts
% ln -s /usr/local/share/fonts/type1/showboat.pfb .

Edit Fontmap so Ghostscript knows about the font
% cd /usr/local/share/ghostscript/4.01
% ex Fontmap
:$a
/Showboat      (showboat.pfb) -; % From CICA /fonts/atm/showboat
.
:wq

Use Ghostscript to examine the font
% gs prfont.ps
Aladdin Ghostscript 4.01 (1996-7-10)
```

```

Copyright (C) 1996 Aladdin Enterprises, Menlo Park, CA. All rights
reserved.
This software comes with NO WARRANTY: see the file PUBLIC for details.
Loading Times-Roman font from /usr/local/share/ghostscript/fonts/tir____.pfb...
/1899520 581354 1300084 13826 0 done.
GS>Showboat DoFont
Loading Showboat font from /usr/local/share/ghostscript/fonts/showboat.pfb...
1939688 565415 1300084 16901 0 done.
>>showpage, press <return> to continue<<
>>showpage, press <return> to continue<<
>>showpage, press <return> to continue<<
GS>quit

```

References: fonts.txt in the Ghostscript 4.01 distribution

7. Using Type 1 Fonts with Groff

Now that the new font can be used by both X11 and Ghostscript, how can one use the new font with groff? First of all, since we are dealing with type 1 PostScript® fonts, the groff device that is applicable is the ps device. A font file must be created for each font that groff can use. A groff font name is just a file in /usr/share/groff_font/devps . With our example, the font file could be /usr/share/groff_font/devps/SHOWBOAT . The file must be created using tools provided by groff.

The first tool is afmtodit. This is not normally installed, so it must be retrieved from the source distribution. I found I had to change the first line of the file, so I did:

```

% cp /usr/src/gnu/usr.bin/groff/afmtodit/afmtodit.pl /tmp
% ex /tmp/afmtodit.pl
:1c
#!/usr/bin/perl -P-
.
:wq

```

This tool will create the groff font file from the metrics file (.afm suffix.) Continuing with our example:

```

Many .afm files are in Mac format... ^M delimited lines
We need to convert them to UNIX® style ^J delimited lines
% cd /tmp
% cat /usr/local/share/fonts/type1/showboat.afm |
tr '\015' '\012' >showboat.afm

Now create the groff font file
% cd /usr/share/groff_font/devps
% /tmp/afmtodit.pl -d DESC -e text.enc /tmp/showboat.afm generate/textmap SHOWBOAT

```

The font can now be referenced with the name SHOWBOAT.

If Ghostscript is used to drive the printers on the system, then nothing more needs to be done. However, if true PostScript® printers are used, then the font must be downloaded to the printer in order for the font to be used (unless the printer happens to have the showboat font built in or on an accessible font disk.) The final step is to create a downloadable font. The pfbtops tool is used to create the .pfa format of the font, and download is modified to reference the new font. The download must reference the internal name of the font. This can easily be determined from the groff font file as illustrated:

```

Create the .pfa font file
% pfbtops /usr/local/share/fonts/type1/showboat.pfb >showboat.pfa

```

Of course, if .pfa is already available, just use a symbolic link to reference it.

```

Get the internal font name
% fgrep internalname SHOWBOAT

```

```

internalname Showboat

Tell groff that the font must be downloaded
% ex download
:$a
Showboat      showboat.pfa
.
:wq

```

To test the font:

```

% cd /tmp
% cat >example.t <<EOF
.sp 5
.ps 16
This is an example of the Showboat font:
.br
.ps 48
.vs (\n(.s+2)p
.sp
.ft SHOWBOAT
ABCDEFGHI
.br
JKLMNOPQR
.br
STUVWXYZ
.sp
.ps 16
.vs (\n(.s+2)p
.fp 5 SHOWBOAT
.ft R
To use it for the first letter of a paragraph, it will look like:
.sp 50p
\s(48\f5H\s0\fRere is the first sentence of a paragraph that uses the
showboat font as its first letter.
Additional vertical space must be used to allow room for the larger
letter.
EOF
% groff -Tps example.t >example.ps

To use ghostscript/ghostview
% ghostview example.ps

To print it
% lpr -Ppostscript example.ps

```

References: [/usr/src/gnu/usr.bin/groff/afmtodit/afmtodit.man](#) , [groff_font\(5\)](#), [groff_char\(7\)](#), [pfbtops\(1\)](#).

8. Converting TrueType Fonts to a groff/PostScript Format For groff

This potentially requires a bit of work, simply because it depends on some utilities that are not installed as part of the base system. They are:

ttf2pf

TrueType to PostScript conversion utilities. This allows conversion of a TrueType font to an ascii font metric (.afm) file.

Currently available at <http://sunsite.icm.edu.pl/pub/GUST/contrib/BachoTeX98/ttf2pf/> . Note: These files are PostScript programs and must be downloaded to disk by holding down Shift when clicking on the link. Otherwise, your browser may try to launch ghostview to view them.

The files of interest are:

- GS_TTF.PS
- PF2AFM.PS
- ttf2pf.ps

The funny upper/lower case is due to their being intended also for DOS shells. `ttf2pf.ps` makes use of the others as upper case, so any renaming must be consistent with this. (Actually, `GS_TTF.PS` and `PFS2AFM.PS` are supposedly part of the Ghostscript distribution, but it is just as easy to use these as an isolated utility. FreeBSD does not seem to include the latter.) You also may want to have these installed to `/usr/local/share/groff_font/devps(?)`.

afmtodit

Creates font files for use with groff from ascii font metrics file. This usually resides in the directory, `/usr/src/contrib/groff/afmtodit`, and requires some work to get going.



Note

If you are paranoid about working in the `/usr/src` tree, simply copy the contents of the above directory to a work location.

In the work area, you will need to make the utility. Just type:

```
# make -f Makefile.sub afmtodit
```

You may also need to copy `/usr/contrib/groff/devps/generate/textmap` to `/usr/share/groff_font/devps/generate` if it does not already exist.

Once all these utilities are in place, you are ready to commence:

1. Create `.afm` by typing:

```
% gs -dNODISPLAY -q -- ttf2pf.ps TTF_name PS_font_name AFM_name
```

Where, `TTF_name` is your TrueType font file, `PS_font_name` is the file name for `.pfa`, `AFM_name` is the name you wish for `.afm`. If you do not specify output file names for the `.pfa` or `.afm` files, then default names will be generated from the TrueType font file name.

This also produces a `.pfa`, the ascii PostScript font metrics file (`.pfb` is for the binary form). This will not be needed, but could (I think) be useful for a fontserver.

For example, to convert the 30f9 Barcode font using the default file names, use the following command:

```
% gs -dNODISPLAY -- ttf2pf.ps 30f9.ttf
Aladdin Ghostscript 5.10 (1997-11-23)
Copyright (C) 1997 Aladdin Enterprises, Menlo Park, CA. All rights reserved.
This software comes with NO WARRANTY: see the file PUBLIC for details.
Converting 30f9.ttf to 30f9.pfa and 30f9.afm.
```

If you want the converted fonts to be stored in `A.pfa` and `B.afm`, then use this command:

```
% gs -dNODISPLAY -- ttf2pf.ps 30f9.ttf A B
Aladdin Ghostscript 5.10 (1997-11-23)
Copyright (C) 1997 Aladdin Enterprises, Menlo Park, CA. All rights reserved.
This software comes with NO WARRANTY: see the file PUBLIC for details.
Converting 30f9.ttf to A.pfa and B.afm.
```

2. Create the groff PostScript file:

Change directories to `/usr/share/groff_font/devps` so as to make the following command easier to execute. You will probably need root privileges for this. (Or, if you are paranoid about working there, make sure you reference the files `DESC`, `text.enc` and `generate/textmap` as being in this directory.)

```
% afmtodit -d DESC -e text.enc file.afm generate/textmap PS_font_name
```

Where, `file.afm` is the `AFM_name` created by `ttf2pf.ps` above, and `PS_font_name` is the font name used from that command, as well as the name that `groff(1)` will use for references to this font. For example, assuming you used the first `tiff2pf.ps` above, then the 3of9 Barcode font can be created using the command:

```
% afmtodit -d DESC -e text.enc 3of9.afm generate/textmap 3of9
```

Ensure that the resulting `PS_font_name` file (e.g., `3of9` in the example above) is located in the directory `/usr/share/groff_font/devps` by copying or moving it there.

Note that if `ttf2pf.ps` assigns a font name using the one it finds in the TrueType font file and you want to use a different name, you must edit the `.afm` prior to running `afmtodit`. This name must also match the one used in the Fontmap file if you wish to pipe `groff(1)` into `gs(1)`.

9. Can TrueType Fonts be Used with Other Programs?

The TrueType font format is used by Windows, Windows 95, and Mac's. It is quite popular and there are a great number of fonts available in this format.

Unfortunately, there are few applications that I am aware of that can use this format: Ghostscript and Povray come to mind. Ghostscript's support, according to the documentation, is rudimentary and the results are likely to be inferior to type 1 fonts. Povray version 3 also has the ability to use TrueType fonts, but I rather doubt many people will be creating documents as a series of raytraced pages :-).

This rather dismal situation may soon change. The [FreeType Project](#) is currently developing a useful set of FreeType tools:

- The `xfstt` font server for X11 can serve TrueType fonts in addition to regular fonts. Though currently in beta, it is said to be quite usable. See [Juliusz Chroboczek's page](#) for further information. Porting instructions for FreeBSD can be found at [Stephen Montgomery's software page](#).
- `xfstt` is another font server for X11, available under `ftp://sunsite.unc.edu/pub/Linux/X11/fonts/` .
- A program called `ttf2bdf` can produce BDF files suitable for use in an X environment from TrueType files. Linux binaries are said to be available from `ftp://crl.nmsu.edu/CLR/multiling/General/` .
- and others ...

10. Where Can Additional Fonts be Obtained?

Many fonts are available on the Internet. They are either entirely free, or are share-ware. In addition many fonts are available in the `x11-fonts/` category in the ports collection

11. Additional Questions

- What use are the `.pfm` files?
- Can one generate the `.afm` from a `.pfa` or `.pfb`?
- How to generate the groff character mapping files for PostScript fonts with non-standard character names?

- Can xditview and devX?? devices be set up to access all the new fonts?
- It would be good to have examples of using TrueType fonts with Povray and Ghostscript.