PDF Links and Forms

2. xkeyval KVP: When the useui option is taken, key-value pairs are de“ned of the form F /T>[= <value>]

2. An array of strings:

   (item1)(item2)...(itemn)

   In this case, the export value is the same as the appearance text.

Default Appearance: The default appearance of a standard list box is determined by the following:

\W{1}\S{I}\F{\FPrint}\BC{0 0 0}

The JavaScript action for the button is given below:

```
\begin{defineJS}{\getComboJS}
var f = this.getField("myCombo");
var a = f.currentValueIndices;
if ( a == -1 )
      app.alert("You•ve typed in \\"" + f.value +"\\".");
else
      app.alert("Selection: " + f.getItemAt(a, false)
            + " (export value: " + f.getItemAt(a, true)+").");
\end{defineJS}
```

2.3. Text Fields

A text “eld is the way a user can enter text into a form.

Form Fields

2. An array of strings:

   (item1)(item2)...(itemn)

   In this case, the export value is the same as the appearance text.

Default Appearance: The default appearance of a standard list box is determined by the following:

\W{1}\S{I}\F{\FPrint}\BC{0 0 0}

2. An array of strings:

   (item1)(item2)...(itemn)

   In this case, the export value is the same as the appearance text.

Default Appearance: The default appearance of a standard list box is determined by the following:

\W{1}\S{I}\F{\FPrint}\BC{0 0 0}