

The `pkgloader` package*

Michiel Helvensteijn
mhelvens+latex@gmail.com

November 30, 2014

Development of this package is organized at github.com/mhelvens/latex-pkgloader.
I am happy to receive feedback there!

1 Introduction

\LaTeX can be extended by loading packages using a `\usepackage`, `\RequirePackage` or `\RequirePackageWithOptions` command. Similarly, documents load a document class using `\documentclass`, `\LoadClass` or `\LoadClassWithOptions`. Packages and classes can add definitions, change existing ones, or otherwise extend functionality of the language.

While the Turing-complete power of the \TeX language is quite useful at times, it does make it all too easy for independent package authors to step on each others toes. CTAN is full of conceptually independent packages that cannot be loaded together, or break if they are not loaded in a specific order.

Yet, until now, there has been no automated package management to speak of. Document authors are usually told to avoid certain package combinations, or to load packages in some specific order. Occasionally, package authors patch their code to be aware of specific other packages, circumventing known conflicts. But this makes maintenance more difficult, because these package authors are ‘mixing concerns’; they put code related to other packages into their own package. And it is all done in an ad-hoc fashion.

Enter `pkgloader`.

1.1 Package Description

Here is an example of main file for a \LaTeX document which uses `pkgloader`:

```
1 \RequirePackage{pkgloader}
2   \documentclass{article}
3   \usepackage{algorithm}
4   \usepackage{hyperref}
5   \usepackage{float}
6 \LoadPackagesNow
7   \vdots
8 \begin{document} ... \end{document}
```

} *any order*

} *optional*

*This document corresponds to `pkgloader` v0.5.0, dated 2014/11/30.

The idea is to load `pkgloader` before loading any other package or class. It can then intercept all loading requests, analyze them and load them properly, taking this burden off the shoulders of the average document author.

Between the second and fifth line, the loading of all packages and classes is postponed. The `\LoadPackagesNow` command then loads the packages in some valid order. This also happens automatically upon reaching the end of the preamble. During this process, ‘conflict resolving’ code may also be run, meant specifically to make other packages work together properly. If the above code were compiled without `pkgloader`, the given package order would cause errors. The main advantage to this approach is that the complexity of dealing with package conflicts is moved to the `pkgloader` package and handled in a systematic manner.

If you are a document author, this may be all you need to know to use `pkgloader`. If you are interested in more advanced functionality, read on!

1.2 The `pkgloader` Area

```
\RequirePackage {pkgloader} ... \LoadPackagesNow
```

The `pkgloader` area is the area between `\RequirePackage{pkgloader}` and `\LoadPackagesNow`. Within it, the three traditional package-loading commands are ‘hijacked’, recording information rather than loading packages directly. Also, a `\Load` command is available, which offers more flexibility in regulating package loading behavior.

`pkgloader` accepts sets of rules coming from outside packages, though support is still somewhat limited. Any `pkgloader-⟨something⟩.sty` file can be loaded within the `pkgloader` area by passing `⟨something⟩` as a package option. The file `pkgloader-recommended.sty` is loaded this way by default. You can overwrite this by passing `recommended=false` as an option. For example:

```
1 \RequirePackage[recommended=false, my-better-rules]{pkgloader}
2     ⋮
3 \LoadPackagesNow
```

This area does not play by the recommended package loading rules, but uses the rules in `pkgloader-my-better-rules.sty` instead.

1.3 Package / Class Loading Requests

<pre>\usepackage \RequirePackage \RequirePackageW...s \documentclass \LoadClass \LoadClassW...s</pre>	<p>For requesting specific packages or classes inside the <code>pkgloader</code> area, just use the commands always used for this purpose: <code>\usepackage</code>, <code>\RequirePackage</code> and <code>\RequirePackageWithOptions</code>, as well as <code>\documentclass</code>, <code>\LoadClass</code> and <code>\LoadClassWithOptions</code>. Their syntax and effective semantics are the same as they have always been. Their effects are just delayed, reordered and perhaps modified by the active <i>package loading rules</i>.</p>
---	---

1.4 Package Loading Rules

`\Load` Each invocation of the `\Load` command sets up a rule about a class, package or packages, which are not necessarily ever loaded. These rules can come from any number of different sources. A central registry will be maintained together with `pkgloader` itself in the form of `pkgloader-recommended.sty`, specifying well-known conflicts

and resolutions. Individual package authors, however, can supply their own rules, as can document authors. Though ideally, for the average document author, things should ‘just work’.

The `\Load` command expects the following syntax:

```

⟨load⟩ ::= \Load ⟨package⟩ ⟨clause⟩1 ... ⟨clause⟩i
          | \Load class ⟨package⟩ ⟨clause⟩1 ... ⟨clause⟩i
          | \Load error   ⟨clause⟩1 ... ⟨clause⟩i

⟨package⟩ ::= [ ⟨options⟩ ] { ⟨pkg⟩ } [ ⟨version⟩ ]

⟨clause⟩ ::= ⟨order⟩ | ⟨condition⟩ | ⟨reason⟩

⟨order⟩ ::= before { ⟨pkg⟩1, ..., ⟨pkg⟩j }
          | after { ⟨pkg⟩1, ..., ⟨pkg⟩j }
          | early
          | late

⟨condition⟩ ::= always | if loaded | if { ⟨ϕ⟩ }

⟨ϕ⟩ ::= ⟨pkg⟩ | ⟨ϕ⟩ && ⟨ϕ⟩ | ⟨ϕ⟩ || ⟨ϕ⟩ | !⟨ϕ⟩ | (⟨ϕ⟩)

⟨reason⟩ ::= because { ⟨token-list⟩ }

```

`⟨pkg⟩` represents a package or class name. `⟨token-list⟩` should expand to a human-readable text without formatting.

if The `⟨condition⟩` clause determines under which package loading conditions any and all parts of a rule are invoked. Here is an example of the use of the `⟨condition⟩` clause:

```

1 \Load {res-ie-1st} if {inputenc && listings}
2 \Load {fixltx2e}  always

```

`res-ie-1st` (a fictional package built specifically to resolve the conflict between `inputenc` and `listings`) will be loaded if requested specifically, or if both `inputenc` and `listings` are loaded. The `fixltx2e` package is always loaded, as it was created to smooth over some mistakes in the L^AT_EX_{2 ϵ} core.

always The **always** keyword makes a rule unconditional. The **if loaded** directive makes a rule conditional on its package already being loaded anyway. This can be used to order two packages only when they are being loaded by other means, and is actually the default behavior (in other words, **if loaded** really does nothing).

before The **before** and **after** keywords should be pretty straightforward. They can be used for things like:

```

1 \Load {xltextra} after {graphicx}

```

which fixes the loading order between these two packages when they are both loaded.

early But the set of L^AT_EX packages is constantly growing, and it appears that some big packages should almost always be loaded early in the process, and others should almost always be loaded late. Therefore the **early** and **late** stages are provided as a fallback mechanism. If two packages are not related by an explicit application order, their loading order may still be decided by their relative stages: **early** before ‘normal’ before **late**. That way, conflicts may be avoided in a majority of cases. This is implemented with `pkgloader-early` and `pkgloader-late` stubs in the loading order graph.

The following example uses the `⟨order⟩` clause in addition to the `⟨condition⟩` clause:

```

1 \Load {res-ie-1st} if {inputenc && listings}
2           after {inputenc , listings}
3 \Load {fixltx2e} always early

```

An important observation about the loading order is that it might form a cycle when contradictory ordering rules are specified:

```

1 \Load {pkg1} after {pkg2}
2 \Load {pkg2} after {pkg1}

```

In practice this could happen if the authors of `pkg1` and `pkg2` independently discover a conflict, and both try to solve it by patching their code and having their own package be loaded last. `pkgloader` can provide a clear error message when this happens, allowing the two package authors to seek contact and collaborate on a solution.

error Now, about the **error** keyword. Initially all package combinations are valid. But if two packages are irredeemably incompatible, their combination can be made to trigger an error message by a command such as the following:

```

1 \Load error if {algorithms && pseudocode}

```

These two packages provide almost identical functionality and conflict on many command-names. It was generally agreed upon that they should never be loaded together. Document authors should simply choose one or the other.

because Finally, the *reason* clause can be used to supply a human-readable explanation of a rule. We finish the above examples by providing reasons:

```

1 \Load {res-ie-1st} if {inputenc && listings}
2           after {inputenc , listings}
3           because {it allows the use of 1 byte unicode
4                   characters in code listings}
5
6 \Load {fixltx2e} always early
7           because {it fixes some imperfections in LaTeX2e}
8
9 \Load error when {algorithms && pseudocode}
10          because {they provide almost identical functionality
11                  and conflict on many command names}

```

In the future, reasons will be extracted automatically to generate documentation. For now, they are displayed with error messages related to the rule in question.

1.5 Status

So far, `pkgloader` seems to work as expected, but has not yet been tested as extensively as it should be. Therefore, bug-reports on the `pkgloader` issue tracker on Github would be most welcome. Also, lots more recommended package loading rules are needed.

I nonetheless decided to publish the package now, because I've been promising to do so for a while now:

<http://tex.stackexchange.com/questions/123174>

I hope that, with feedback and community collaboration, use of this package will become widespread and package authors will be able to work in a more modular fashion.

Future versions of `pkgloader` will be able to intelligently merge package options and to track packages loaded by other packages in order to better inform the user — perhaps even fix problems by carrying information into the next run through auxiliary files. But most of this will depend on feedback.

2 Implementation

We now show and explain the entire implementation from `pkgloader.sty`.

2.1 Package Info

First, the mandatory package meta-information:

```
1 \NeedsTeXFormat{LaTeX2e}
2 \RequirePackage{expl3}
3 \ProvidesExplPackage{pkgloader}{2014/11/30}{0.5.0}
4 {managing the options and loading order of LaTeX packages}
```

2.2 Required Packages

The following packages are required. Two standard `expl3`-related packages, one experimental package in `l3regex` and one user-contributed `expl3` package in `lt3graph`:

```
5 \RequirePackage{xparse}
6 \RequirePackage{l3keys2e}
7 \RequirePackage{l3regex}
8 \RequirePackage{lt3graph}
```

2.3 Package Code

We need two global data-structures. One to keep track of all packages that are known, one to keep track of the packages that are actually going to be loaded, and their order:

```
9 \prop_new:N \g__pkgloader_known_pkg_prop
10 \graph_new:N \g__pkgloader_pkg_graph
```

We store pristine versions of the three package loading commands:

```
11 \cs_gset_eq:NN \__pkgloader_usepkg:wnw \usepackage
12 \cs_gset_eq:NN \__pkgloader_RPkg:wnw \RequirePackage
13 \cs_gset_eq:NN \__pkgloader_RPkgWithOptions:wnw \RequirePackageWithOptions
14 \cs_gset_eq:NN \__pkgloader_doccls:wnw \documentclass
15 \cs_gset_eq:NN \__pkgloader_LCls:wnw \LoadClass
16 \cs_gset_eq:NN \__pkgloader_LClsWithOptions:wnw \LoadClassWithOptions
```

And we define a command to clean up any and all commands that we change or introduce. It will be called when they are not needed anymore:

```
17 \tl_new:N \__pkgloader_cleanup_commands:
18 \tl_put_right:Nn \__pkgloader_cleanup_commands: {
19   \cs_gset_eq:NN \usepackage \__pkgloader_usepkg:wnw
20   \cs_gset_eq:NN \RequirePackage \__pkgloader_RPkg:wnw
21   \cs_gset_eq:NN \RequirePackageWithOptions \__pkgloader_RPkgWithOptions:wnw
22   \cs_gset_eq:NN \documentclass \__pkgloader_doccls:wnw
23   \cs_gset_eq:NN \LoadClass \__pkgloader_LCls:wnw
24   \cs_gset_eq:NN \LoadClassWithOptions \__pkgloader_LClsWithOptions:wnw
25 }
```

This function globally registers a package loading rule, which can be created with either the `\Load` command or any of the hijacked `\usepackage`-like commands:

```

26 \cs_new_protected:Nn \__pkgloader_register_rule:nnnnnnnn {
27   % #1: package or class name
28   % #2: options
29   % #3: version
30   % #4: condition
31   % #5: compiled condition
32   % #6: packages to load before this one
33   % #7: packages to load after this one
34   % #8: reason
35   % #9: command

```

If this package or class hasn't been seen before, register it and create a rule-counter for it:

```

36 \prop_if_in:NnF \g__pkgloader_known_pkg_prop {#1} {
37   \prop_gput:Nnn \g__pkgloader_known_pkg_prop {#1} {}
38   \int_new:c {g__pkgloader_count_{#1}_int}
39 }

```

Increment the rule-counter:

```

40 \int_incr:c {g__pkgloader_count_{#1}_int}

```

Then, we set all properties of the

```

41 \tl_set:Nf \l_tmpa_tl {\int_use:c {g__pkgloader_count_{#1}_int}}
42 \tl_set:cn {g__pkgloader_options_{#1}_{\l_tmpa_tl}_tl} {#2}
43 \tl_set:cn {g__pkgloader_version_{#1}_{\l_tmpa_tl}_tl} {#3}
44 \tl_set:cn {g__pkgloader_condition_{#1}_{\l_tmpa_tl}_tl} {#4}
45 \tl_set:cn {g__pkgloader_compiled_condition_{#1}_{\l_tmpa_tl}_tl} {#5}
46 \tl_set:cn {g__pkgloader_predecessors_{#1}_{\l_tmpa_tl}_tl} {#6}
47 \tl_set:cn {g__pkgloader_successors_{#1}_{\l_tmpa_tl}_tl} {#7}
48 \tl_set:cn {g__pkgloader_reason_{#1}_{\l_tmpa_tl}_tl} {#8}
49 \tl_set:cn {g__pkgloader_command_{#1}_{\l_tmpa_tl}_tl} {#9}
50 \bool_new:c {g__pkgloader_used_{#1}_{\l_tmpa_tl}_bool}
51 }

```

These six macros are redefined to just register the loading information rather than load the package or class immediately. The distinction between package and class is made by prefixing the name with either `.sty` or `.cls` (which will be stripped off before the file is actually loaded):

```

52 \RenewDocumentCommand {\usepackage} { o m o }
53   { \__pkgloader_usepackage_cmd:nnnnnn
54     {\usepackage} {#1} {#2.sty} {#3}
55     {pkgloader-cls-pkg.sty} {} }
56 \RenewDocumentCommand {\RequirePackage} { o m o }
57   { \__pkgloader_usepackage_cmd:nnnnnn
58     {\RequirePackage} {#1} {#2.sty} {#3}
59     {} {} }
60 \RenewDocumentCommand {\RequirePackageWithOptions} { o m o }

```

```

61 { \__pkgloader_usepackage_cmd:nnnnnn
62   {\RequirePackageWithOptions} {#1} {#2.sty} {#3}
63   {} {} }
64 \RenewDocumentCommand {\documentclass} { o m o }
65 { \__pkgloader_usepackage_cmd:nnnnnn
66   {\documentclass} {#1} {#2.cls} {#3}
67   {} {pkgloader-cls-pkg.sty} }
68 \RenewDocumentCommand {\LoadClass} { o m o }
69 { \__pkgloader_usepackage_cmd:nnnnnn
70   {\LoadClass} {#1} {#2.cls} {#3}
71   {} {pkgloader-cls-pkg.sty} }
72 \RenewDocumentCommand {\LoadClassWithOptions} { o m o }
73 { \__pkgloader_usepackage_cmd:nnnnnn
74   {\LoadClassWithOptions} {#1} {#2.cls} {#3}
75   {} {pkgloader-cls-pkg.sty} }

```

Storing this information is delegated to the `__pkgloader_register_rule:nnnnnnnn` function:

```

76 \cs_new:Nn \__pkgloader_usepackage_cmd:nnnnnn {
77   \__pkgloader_register_rule:nnnnnnnn
78   {#3} {#2} {#4}           % package name, options, version
79   {pkgloader-true.sty}    % condition
80   {\c_true_bool}         % compiled condition
81   {#5} {#6}              % predecessors, successors
82   {it~is~requested~by~the~author} % reason
83   {#1}                   % command
84 }

```

This is a sophisticated user-level command for manipulating package loading order and conditions. It has a ‘non-standard’ but convenient syntax, which scans for clauses rather than taking standard parameters:

```

85 \NewDocumentCommand {\Load} {} {

```

Initialize the variables used for storing given data:

```

86 \tl_clear:N \l__pkgloader_load_extension_tl
87 \tl_clear:N \l__pkgloader_load_options_tl
88 \tl_clear:N \l__pkgloader_load_name_tl
89 \tl_clear:N \l__pkgloader_load_version_tl
90 \clist_clear:N \l__pkgloader_load_pred_clist
91 \clist_clear:N \l__pkgloader_load_succ_clist
92 \tl_clear:N \l__pkgloader_load_cond_tl
93 \tl_clear:N \l__pkgloader_load_because_tl
94 \tl_clear:N \l__pkgloader_load_cmd_tl
95 \bool_set_false:N \l__pkgloader_early_late_used_bool

```

Start scanning for input:

```

96 \__pkgloader_load_scan_ext_:w

```



```

174 }}}}
175 }

```

This processes the “always” clause, which loads this package conditional on the “pkgloader-true” package being loaded (which always is):

```

176 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_al:w ways {
177   \tl_put_right:Nn \l__pkgloader_load_cond_tl {~||~pkgloader-true}
178   \__pkgloader_load_scan_clause_w
179 }

```

This processes the “after” clause:

```

180 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_af:w ter #1 {
181   \clist_map_inline:nn {#1} {
182     \clist_put_right:Nn \l__pkgloader_load_pred_clist {##1.sty}
183   }
184   \__pkgloader_load_scan_clause_w
185 }

```

This processes the “because” clause:

```

186 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_bec:w ause #1 {
187   \tl_set:Nn \l__pkgloader_load_because_tl {#1}
188   \__pkgloader_load_scan_clause_w
189 }

```

This processes the “before” clause:

```

190 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_bef:w ore #1 {
191   \clist_map_inline:nn {#1} {
192     \clist_put_right:Nn \l__pkgloader_load_succ_clist {##1.sty}
193   }
194   \__pkgloader_load_scan_clause_w
195 }

```

This processes the “early” clause, which orders this package before the “pkgloader-early” stub:

```

196 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_e:w arly {
197   \bool_set_true:N \l__pkgloader_early_late_used_bool
198   \clist_put_right:Nn \l__pkgloader_load_succ_clist {pkgloader-early.sty}
199   \__pkgloader_load_scan_clause_w
200 }

```

This processes the “if” clause, which may still be a manual condition or the “loaded” keyword:

```

201 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_i:w f {
202   \peek_charcode_remove_ignore_spaces:NTF l {
203     \__pkgloader_load_scan_clause_if_l:w
204   }{
205     \__pkgloader_load_scan_clause_if_nw

```

```

206 }
207 }

```

This processes the “if loaded” clause, which uses this package being loaded as the condition for the rule being used:

```

208 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_if_l:w oaded {
209   \tl_put_right:Nn \l__pkgloader_load_cond_tl {~||~}
210   \tl_put_right:NV \l__pkgloader_load_cond_tl \l__pkgloader_load_name_tl
211   \__pkgloader_load_scan_clause_w
212 }

```

This processes the “if” clause with a manual condition:

```

213 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_if_:nw #1 {
214   \tl_put_right:Nn \l__pkgloader_load_cond_tl {~||~#1}
215   \__pkgloader_load_scan_clause_w
216 }

```

This processes the “late” clause, which orders this package after the “pkgloader-late” stub:

```

217 \cs_new_protected_nopar:Npn \__pkgloader_load_scan_clause_l:w ate {
218   \bool_set_true:N \l__pkgloader_early_late_used_bool
219   \clist_put_right:Nn \l__pkgloader_load_pred_clist {pkgloader-late.sty}
220   \__pkgloader_load_scan_clause_w
221 }

```

This function processes the collected data and registers it:

```

222 \cs_new_protected_nopar:Nn \__pkgloader_load_end: {

```

We remove the leading “ || ” from the condition:

```

223   \tl_remove_once:Nn \l__pkgloader_load_cond_tl {~||~}

```

If no condition is given at all, the default is: “if loaded”

```

224   \tl_if_empty:NT \l__pkgloader_load_cond_tl
225     { \tl_set_eq:NN \l__pkgloader_load_cond_tl \l__pkgloader_load_name_tl }

```

We now take the condition and compile it to a `\bool_if:` kind of syntax. The original syntax is preserved to use in error messages and such:

```

226   \tl_set_eq:NN \l__pkgloader_load_compiled_cond_tl \l__pkgloader_load_cond_tl
227   \regex_replace_all:nnN
228     { [^&|\|(\)\!\s]+ }
229     { (\c{graph_if_vertex_exist_p:Nn}
230       \c{g__pkgloader_pkg_graph}\cB\{\0\}.sty\cE\} ) }
231   \l__pkgloader_load_compiled_cond_tl

```

If no reason was given for this rule, it was obviously ‘because of reasons’:

```

232 \tl_if_empty:NT \l__pkgloader_load_because_tl
233   { \tl_set:Nn \l__pkgloader_load_because_tl {of~reasons} }

```

Having gathered and processed the data, the rule is registered:

```

234 \__pkgloader_register_rule:VVVVVVVVV
235   \l__pkgloader_load_name_tl
236   \l__pkgloader_load_options_tl
237   \l__pkgloader_load_version_tl
238   \l__pkgloader_load_cond_tl
239   \l__pkgloader_load_compd_cond_tl
240   \l__pkgloader_load_pred_clist
241   \l__pkgloader_load_succ_clist
242   \l__pkgloader_load_because_tl
243   \l__pkgloader_load_cmd_tl
244 }
245 \cs_generate_variant:Nn \tl_if_eq:nnF {NnF}
246 \cs_generate_variant:Nn \graph_gput_vertex:Nn {NV}
247 \cs_generate_variant:Nn \graph_gput_edge:Nnn {NnV,NVn}
248 \cs_generate_variant:Nn \seq_gput_right:Nn {NV}
249 \cs_generate_variant:Nn \__pkgloader_register_rule:nnnnnnnnn {VVVVVVVVVV}
250 \tl_new:N \l__pkgloader_load_extension_tl
251 \tl_new:N \l__pkgloader_load_options_tl
252 \tl_new:N \l__pkgloader_load_name_tl
253 \tl_new:N \l__pkgloader_load_version_tl
254 \clist_new:N \l__pkgloader_load_pred_clist
255 \clist_new:N \l__pkgloader_load_succ_clist
256 \tl_new:N \l__pkgloader_load_cond_tl
257 \tl_new:N \l__pkgloader_load_because_tl
258 \tl_new:N \l__pkgloader_load_cmd_tl
259 \bool_new:N \l__pkgloader_early_late_used_bool

```

And here's the instruction to clean up the `\Load` command-name at the end:

```

260 \tl_put_right:Nn \__pkgloader_cleanup_commands:
261   { \cs_undefine:N \Load }

```

This function decides, based on all loaded rules and package requests, which packages, options and versions end up being loaded, and in which order.

```

262 \cs_new_protected:Nn \__pkgloader_select_packages: {

```

We first set up a graph to record accepted orderings:

```

263 \graph_clear:N \l__pkgloader_order_graph

```

We then start a loop that runs at least once, then repeats while additional package configurations are still being added to the set. Eventually the loop reaches a fixed point and terminates.

```

264 \bool_do_while:Nn \l__pkgloader_selection_changed_bool {
265   \bool_set_false:N \l__pkgloader_selection_changed_bool

```

Then first, for all possible package configurations (a nested loop, but not doubly indented because it feels like one loop):

```

266   \prop_map_inline:Nn \g__pkgloader_known_pkg_prop {%%%%%%%%%%%% %% #1
267   \int_step_inline:nncn {1} {1} {g__pkgloader_count_{##1}_int} {%% #####1

```

If the current configuration should be loaded but still isn't selected (nested conditional; but again, not indented):

```

268   \bool_if:cF {g__pkgloader_used_{##1}_{#####1}_bool} {
269   \bool_if:vT {g__pkgloader_compiled_condition_{##1}_{#####1}_t1} {

```

We mark the package configuration as being used:

```

270   \bool_set_true:c {g__pkgloader_used_{##1}_{#####1}_bool}

```

We record the configuration in the main package graph, which maps each package to a clist of selected configurations:

```

271   \graph_get_vertex:NnNTF \g__pkgloader_pkg_graph {##1}
272   \l__pkgloader_used_configs_t1 {
273   \tl_if_empty:NTF \l__pkgloader_used_configs_t1
274   { \graph_gput_vertex:Nnf \g__pkgloader_pkg_graph {##1} {#####1} }
275   { \graph_gput_vertex:Nnf \g__pkgloader_pkg_graph {##1}
276   { \l__pkgloader_used_configs_t1, #####1} }
277   } { \graph_gput_vertex:Nnf \g__pkgloader_pkg_graph {##1} {#####1} }

```

In a separate graph, we record the associated (now activated) package loading orders. We don't do this in the main graph, because it may involve packages that are themselves not yet selected. These edges are later filtered and added to the main graph:

```

278   \graph_put_vertex:Nn \l__pkgloader_order_graph {##1}
279   \clist_map_inline:cn {g__pkgloader_predecessors_{##1}_{#####1}_t1} {
280   \graph_put_vertex:Nn \l__pkgloader_order_graph {#####1}
281   \graph_get_edge:NnnNTF \l__pkgloader_order_graph
282   {#####1} {##1} \l__pkgloader_used_configs_t1
283   { \graph_put_edge:Nnnn \l__pkgloader_order_graph
284   {#####1} {##1} {\l__pkgloader_used_configs_t1,#####1} }
285   { \graph_put_edge:Nnnn \l__pkgloader_order_graph
286   {#####1} {##1} {#####1} }
287   }
288   \clist_map_inline:cn {g__pkgloader_successors_{##1}_{#####1}_t1} {
289   \graph_put_vertex:Nn \l__pkgloader_order_graph {#####1}
290   \graph_get_edge:NnnNTF \l__pkgloader_order_graph
291   {##1} {#####1} \l__pkgloader_used_configs_t1
292   { \graph_put_edge:Nnnn \l__pkgloader_order_graph
293   {##1} {#####1} {\l__pkgloader_used_configs_t1,#####1} }
294   { \graph_put_edge:Nnnn \l__pkgloader_order_graph

```

```

295         {##1} {#####1}                               {#####1} }
296     }

```

We then mark the change, so a next iteration will be entered:

```

297     \bool_set_true:N \l__pkgloader_selection_changed_bool
298 }}
299 }}
300 }

```

We put the applicable proposed orderings into the graph of selected packages:

```

301 \graph_gput_edges_from:NN \g__pkgloader_pkg_graph \l__pkgloader_order_graph

```

If there is a cycle in the derived package loading order: ERROR

```

302 \graph_if_cyclic:NT \g__pkgloader_pkg_graph
303 { \msg_fatal:nn {pkgloader} {cyclic-order} }

```

Finally, we apply some default orderings where needed:

- If a package should not specifically go early or late, it goes inbetween; and
- if a package should not specifically go before a class, it goes after.

```

304 \graph_map_vertices_inline:Nn \g__pkgloader_pkg_graph {
305   \seq_if_in:NnF \g__pkgloader_system_packages_seq {##1} {
306     \graph_acyclic_if_path_exist:NnnF \g__pkgloader_pkg_graph
307       {##1} {pkgloader-early.sty} {
308       \graph_acyclic_if_path_exist:NnnF \g__pkgloader_pkg_graph
309         {pkgloader-late.sty} {##1} {
310         \graph_put_edge:Nnn \g__pkgloader_pkg_graph {pkgloader-early.sty} {##1}
311         \graph_put_edge:Nnn \g__pkgloader_pkg_graph {##1} {pkgloader-late.sty}
312       } }
313     \graph_acyclic_if_path_exist:NnnF \g__pkgloader_pkg_graph
314       {##1} {pkgloader-cls-pkg.sty} {
315       \graph_put_edge:Nnn \g__pkgloader_pkg_graph {pkgloader-cls-pkg.sty} {##1}
316     } } }
317 }
318 \cs_generate_variant:Nn \int_step_inline:nnnn {nncn}
319 \cs_generate_variant:Nn \bool_if:nT {vT}
320 \cs_generate_variant:Nn \withargs:nnn {vvn}
321 \cs_generate_variant:Nn \graph_gput_vertex:Nnn {Nnf}
322 \graph_new:N \l__pkgloader_order_graph
323 \tl_new:N \l__pkgloader_used_configs_tl
324 \bool_new:N \l__pkgloader_selection_changed_bool

```

Now follows the user command to consolidate all package loading requests and do the ‘right thing’ (tm). Invoking this command ends the work of `pkgloader`.

```
325 \NewDocumentCommand {\LoadPackagesNow} {} {
```

We first select package configurations by their loading conditions:

```
326 \__pkgloader_select_packages:
```

Now to clean up after pkgloader, restoring and removing various command-names.

```
327 \__pkgloader_cleanup_commands:
```

Then, for all used packages, in topological order...

```
328 \graph_map_topological_order_inline:Nn \g__pkgloader_pkg_graph {
```

...load that package. Though note that this code is still quite incomplete, because it loads the first viable configuration. It should:

1. use the `WithOptions` version of the command if necessary,
2. allow custom merging schemes for options, and
3. use the latest required version.

```
329 \withargs:xn { \clist_item:nn{##2}{1} } {
330 \withargs:vvfvn {g__pkgloader_command_{##1}_{####1}_t1}
331 {g__pkgloader_options_{##1}_{####1}_t1}
332 {\__pkgloader_strip_extension:f{##1}}
333 {g__pkgloader_version_{##1}_{####1}_t1} {
334 \IfValueTF {#####2}
335 { \IfValueTF {#####4}
336 { #####1 [#####2] {#####3} [#####4] }
337 { #####1 [#####2] {#####3} } }
338 { \IfValueTF {#####4}
339 { #####1 {#####3} [#####4] }
340 { #####1 {#####3} } }
341 }
342 }
343 }
344 }
345 \cs_generate_variant:Nn \withargs:n {xn}
346 \cs_generate_variant:Nn \withargs:n {nnnn} {vvfvn}
```

And it needs the following auxiliary function to strip filenames from their four character extension:

```
347 \cs_new:Nn \__pkgloader_strip_extension:f {
348 \tl_reverse:f{
349 \tl_tail:f{\tl_tail:f{\tl_tail:f{\tl_tail:f{
350 \tl_reverse:n{#1}
351 }}}}}
352 }
353 }
```



```
354 \cs_generate_variant:Nn \tl_reverse:n {f}
```

It's a bit clunky. Is there a substring function in `expl3` we could use that I don't know about?

And here's the instruction to clean up the `\LoadPackagesNow` command-name at the end:

```
355 \tl_put_right:Nn \__pkgloader_cleanup_commands:
356 { \cs_undefine:N \LoadPackagesNow }
```

```
357 \cs_gset_eq:NN \__pkgloader_begin_env:n \begin
358 \RenewDocumentCommand {\begin} {m} {
359   \tl_if_eq:nnT {#1} {document} {\LoadPackagesNow}
360   \__pkgloader_begin_env:n {#1}
361 }
362 \tl_put_right:Nn \__pkgloader_cleanup_commands:
363 { \cs_gset_eq:NN \begin \__pkgloader_begin_env:n }
```

Bootstrap `pkgloader` by inserting `pkgloader-true` in the graph directly, so all other packages can be inserted with rules, possibly using the `always` clause.

```
364 \graph_gput_vertex:Nn \g__pkgloader_pkg_graph {pkgloader-true.sty}
```

We keep a list of all `pkgloader` dummy packages:

```
365 \seq_new:N \g__pkgloader_system_packages_seq
366 \cs_generate_variant:Nn \seq_gset_from_clist:Nn {Nx}
367 \seq_gset_from_clist:Nx \g__pkgloader_system_packages_seq
368 {\tl_to_str:n
369  {pkgloader-true.sty,
370   pkgloader-false.sty,
371   pkgloader-early.sty,
372   pkgloader-late.sty,
373   pkgloader-cls-pkg.sty}}
```

We then register the core logical rules of `pkgloader`, regarding fundamental package 'stubs' like `pkgloader-false`, `pkgloader-error`, `pkgloader-early`, and so on.

```
374 \withargs:nn {of~the~mandatory~core~rules~of~pkgloader} {
375   \Load error if {pkgloader-false}           because {#1}
376   \Load {pkgloader-true}                    always      because {#1}
377   \Load {pkgloader-early}                   always      because {#1}
378   \Load {pkgloader-late}                    always      because {#1}
379   \Load {pkgloader-cls-pkg}                 always      because {#1}
380   \Load {pkgloader-early} before {pkgloader-late} because {#1}
381 }
```

We process the options passed to `pkgloader` as `.sty` files to be loaded before `pkgloader` does its thing. This should be used to define new `pkgloader` rules. Note, particularly, that any `\usepackage`-like command inside those `.sty` files is registered and processed by `pkgloader`; not loaded directly.

First, we define the functions used to handle an option.

```

382 \cs_new:Nn \__pkgloader_process_option:n
383   { \__pkgloader_process_option:nn {#1} {true} }
384 \cs_new:Nn \__pkgloader_process_option:nn
385   { \tl_if_eq:nnTF {#2} {true}
386     { \seq_put_right:Nn \l__pkgloader_rule_packages_seq {#1} }
387     { \seq_remove_all:Nn \l__pkgloader_rule_packages_seq {#1} } }

```

The recommended rules are loaded unless explicitly turned off.

```

388 \seq_new:N \l__pkgloader_rule_packages_seq
389 \seq_put_right:Nn \l__pkgloader_rule_packages_seq {recommended}

```

Process the options to populate `\l__pkgloader_rule_packages_seq`.

```

390 \cs_generate_variant:Nn \keyval_parse:NNn {NNv}
391 \keyval_parse:NNv
392   \__pkgloader_process_option:n
393   \__pkgloader_process_option:nn
394   {opt@pkgloader.sty}
395 \seq_remove_duplicates:N \l__pkgloader_rule_packages_seq

```

Actually load the `.sty` files in `\l__pkgloader_rule_packages_seq`. Note that the actual file needs the `pkgloader-` prefix.

```

396 \seq_map_inline:Nn \l__pkgloader_rule_packages_seq
397   { \__pkgloader_RPkg:wvw {pkgloader-#1} }

```

Finally, we make a show of using the proper macros for L^AT_EX's benefit. If we don't, a L^AT_EX error is issued.

```

398 \DeclareOption*{}
399 \ProcessOptions\relax

```

Finally, here are the error messages this package can generate. First a simple error for cycles, which should be improved to show the cause of the cycle.

```

400 \msg_new:nnn {pkgloader} {cyclic-order}
401   { There is a cycle in the requested package loading order. }

```

And the following is the error reported for certain package combinations that have been forbidden through an error rule.

```

402 \msg_new:nnnn {pkgloader} {illegal-combination}
403   { A combination of packages fitting the following condition
404     was requested:
405     \\\ \ \ \ #1 \\\ \
406     This is an error because #2. }
407   { A pkgloader rule was requested that prohibits the logical
408     combination \above for the specified reason. It is probably
409     a good reason. }

```

Change History

0.1.0	General: initial version	1	files; additionally, pkgloader now understands preferred loading orders of cleveref	1
0.2.0	General: an important release, which implements most features described in the pkgloader TUGBoat article, and fixes a ton of bugs	1		
0.3.0	General: fixed the package to work with more recent releases of expl3, which removed the individual l3kernel .sty			
0.4.1	General: integrates a number of new package loading rules contributed by the community	1		
0.5.0	General: integrates a number of new package loading rules contributed by the community	1		

Index

The italic numbers denote the pages where the corresponding entry is described, numbers underlined point to the definition, all others indicate the places where it is used.

Symbols	
\!	228
\&	228
\(228
\)	228
\.	230
\\	405, 408
\{	230
\}	230
__pkgloader_LCIs:wnw	15, 23
__pkgloader_LCIsWithOptions:wnw	16, 24
__pkgloader_RPkg:wnw	12, 20, 397
__pkgloader_RPkgWithOptions:wnw	13, 21
__pkgloader_begin_env:n	357, 360, 363
__pkgloader_cleanup_commands:	17, 18, 260, 327, 355, 362
__pkgloader_doccls:wnw	14, 22
__pkgloader_load_end:	152, 161, 164, 173, 222
__pkgloader_load_scan_clause_:w	124, 138, 143, 145, 178, 184, 188, 194, 199, 211, 215, 220
__pkgloader_load_scan_clause_af:w	150, 180
__pkgloader_load_scan_clause_al:w	148, 176
__pkgloader_load_scan_clause_bec:w	157, 186
__pkgloader_load_scan_clause_bef:w	159, 190
__pkgloader_load_scan_clause_e:w	167, 196
__pkgloader_load_scan_clause_i:w	169, 201
__pkgloader_load_scan_clause_if:nw	205, 213
__pkgloader_load_scan_clause_if_l:w	203, 208
__pkgloader_load_scan_clause_l:w	171, 217
__pkgloader_load_scan_ext:w	96, 98
__pkgloader_load_scan_ext_c:w	100, 107
__pkgloader_load_scan_pkg:nw	119, 128, 130
__pkgloader_load_scan_pkg:w	104, 111, 113
__pkgloader_load_scan_pkg_e:w	115, 122
__pkgloader_load_scan_pkg_options:nw	117, 126
__pkgloader_load_scan_version:nw	136, 141
__pkgloader_process_option:n	382, 392
__pkgloader_process_option:nn	383, 384, 393
__pkgloader_register_rule:VVVVVVVV	234
__pkgloader_register_rule:nnnnnnnn	26, 77, 249
__pkgloader_select_packages:	262, 326
__pkgloader_strip_extension:f	332, 347

<code>__pkgloader_usepackage_cmd:nnnnnn</code>	53, 57, 61, 65, 69, 73, 76	<code>\g__pkgloader_pkg_graph</code>	10, 271, 274, 275, 277, 301, 302, 304, 306, 308, 310, 311, 313, 315, 328, 364
<code>__pkgloader_usepkg:wnw</code>	11, 19	<code>\g__pkgloader_system_packages_seq</code>	305, 365, 367
<code>\ </code>	228	<code>\graph_acyclic_if_path_exist:NnnF</code>	306, 308, 313
Numbers			
<code>\0</code>	230	<code>\graph_clear:N</code>	263
<code>\u</code>	405	<code>\graph_get_edge:NnnNTF</code>	281, 290
B			
<code>\begin</code>	357, 358, 363	<code>\graph_get_vertex:NnNTF</code>	271
<code>\bool_do_while:Nn</code>	264	<code>\graph_gput_edge:Nnn</code>	247
<code>\bool_if:cF</code>	268	<code>\graph_gput_edges_from:NN</code>	301
<code>\bool_if:nT</code>	319	<code>\graph_gput_vertex:Nn</code>	246, 364
<code>\bool_if:vT</code>	269	<code>\graph_gput_vertex:Nnf</code>	274, 275, 277
<code>\bool_new:c</code>	50	<code>\graph_gput_vertex:Nnn</code>	321
<code>\bool_new:N</code>	259, 324	<code>\graph_if_cyclic:NT</code>	302
<code>\bool_set_false:N</code>	95, 265	<code>\graph_map_topological_order_inline:Nn</code>	328
<code>\bool_set_true:c</code>	270	<code>\graph_map_vertices_inline:Nn</code>	304
<code>\bool_set_true:N</code>	197, 218, 297	<code>\graph_new:N</code>	10, 322
C			
<code>\c</code>	229, 230	<code>\graph_put_edge:Nnn</code>	310, 311, 315
<code>\c_true_bool</code>	80	<code>\graph_put_edge:Nnnn</code>	283, 285, 292, 294
<code>\cB</code>	230	<code>\graph_put_vertex:Nn</code>	278, 280, 289
<code>\cE</code>	230	I	
<code>\clist_clear:N</code>	90, 91	<code>\IfValueTF</code>	334, 335, 338
<code>\clist_item:nn</code>	329	<code>\int_incr:c</code>	40
<code>\clist_map_inline:cn</code>	279, 288	<code>\int_new:c</code>	38
<code>\clist_map_inline:nn</code>	181, 191	<code>\int_step_inline:nncn</code>	267
<code>\clist_new:N</code>	254, 255	<code>\int_step_inline:nnnn</code>	318
<code>\clist_put_right:Nn</code> 110, 182, 192, 198, 219		<code>\int_use:c</code>	41
<code>\cs_generate_variant:Nn</code>	245, 246, 247, 248, 249, 318, 319, 320, 321, 345, 346, 354, 366, 390	K	
<code>\cs_gset_eq:NN</code>	11, 12, 13, 14, 15, 16, 19, 20, 21, 22, 23, 24, 357, 363	<code>\keyval_parse:Nnn</code>	390
<code>\cs_new:Nn</code>	76, 347, 382, 384	<code>\keyval_parse:NNv</code>	391
<code>\cs_new_protected:Nn</code>	26, 262	L	
<code>\cs_new_protected_nopar:Nn</code>	222	<code>\l__pkgloader_early_late_used_bool</code>	95, 197, 218, 259
<code>\cs_new_protected_nopar:Npn</code> 98, 107, 113, 122, 126, 130, 141, 145, 176, 180, 186, 190, 196, 201, 208, 213, 217		<code>\l__pkgloader_load_because_tl</code>	93, 187, 232, 233, 242, 257
<code>\cs_undefine:N</code>	261, 356	<code>\l__pkgloader_load_cmd_tl</code>	94, 103, 109, 243, 258
D			
<code>\DeclareOption</code>	398	<code>\l__pkgloader_load_compd_cond_tl</code>	226, 231, 239
<code>\documentclass</code>	14, 22, 64, 66	<code>\l__pkgloader_load_cond_tl</code>	92, 177, 209, 210, 214, 223, 224, 225, 226, 238, 256
G			
<code>\g__pkgloader_known_pkg_prop</code>	9, 36, 37, 266	<code>\l__pkgloader_load_extension_tl</code>	86, 102, 108, 134, 250
		<code>\l__pkgloader_load_name_tl</code>	88, 123, 131, 133, 210, 225, 235, 252
		<code>\l__pkgloader_load_options_tl</code>	87, 127, 236, 251

<code>\l__pkgloader_load_pred_clist</code>	<code>\RequirePackage</code>
. 90, 182, 219, 240, 254 2, 5, 6, 7, 8, 12, 20, 56, 58, 103
<code>\l__pkgloader_load_succ_clist</code>	<code>\RequirePackageWithOptions</code> 13, 21, 60, 62
. 91, 110, 192, 198, 241, 255	
<code>\l__pkgloader_load_version_tl</code>	S
. 89, 142, 237, 253	<code>\s</code> 228
<code>\l__pkgloader_order_graph</code>	<code>\seq_gput_right:Nn</code> 248
. 263, 278, 280, 281,	<code>\seq_gset_from_clist:Nn</code> 366
283, 285, 289, 290, 292, 294, 301, 322	<code>\seq_gset_from_clist:Nx</code> 367
<code>\l__pkgloader_rule_packages_seq</code>	<code>\seq_if_in:NnF</code> 305
. 386, 387, 388, 389, 395, 396	<code>\seq_map_inline:Nn</code> 396
<code>\l__pkgloader_selection_changed_bool</code>	<code>\seq_new:N</code> 365, 388
. 264, 265, 297, 324	<code>\seq_put_right:Nn</code> 386, 389
<code>\l__pkgloader_used_configs_tl</code>	<code>\seq_remove_all:Nn</code> 387
272, 273, 276, 282, 284, 291, 293, 323	<code>\seq_remove_duplicates:N</code> 395
<code>\l_tmpa_tl</code>	T
. 41, 42, 43, 44, 45, 46, 47, 48, 49, 50	<code>\tl_clear:N</code> 86, 87, 88, 89, 92, 93, 94
<code>\Load</code> 85, 261, 375, 376, 377, 378, 379, 380	<code>\tl_if_empty:NT</code> 224, 232
<code>\LoadClass</code> 15, 23, 68, 70, 109	<code>\tl_if_empty:NTF</code> 273
<code>\LoadClassWithOptions</code> 16, 24, 72, 74	<code>\tl_if_eq:nnF</code> 245
<code>\LoadPackagesNow</code> 325, 356, 359	<code>\tl_if_eq:nnT</code> 359
M	<code>\tl_if_eq:nnTF</code> 385
<code>\msg_fatal:nn</code> 303	<code>\tl_new:N</code> 17,
<code>\msg_new:nnn</code> 400	250, 251, 252, 253, 256, 257, 258, 323
<code>\msg_new:nnnn</code> 402	<code>\tl_put_right:Nn</code>
N 18, 177, 209, 214, 260, 355, 362
<code>\NeedsTeXFormat</code> 1	<code>\tl_put_right:NV</code> 132, 210
<code>\NewDocumentCommand</code> 85, 325	<code>\tl_remove_once:Nn</code> 223
P	<code>\tl_reverse:f</code> 348
<code>\peek_charcode_remove:NTF</code>	<code>\tl_reverse:n</code> 350, 354
. 147, 149, 155, 156, 158	<code>\tl_set:cn</code> 42, 43, 44, 45, 46, 47, 48, 49
<code>\peek_charcode_remove_ignore_spaces:NTF</code>	<code>\tl_set:Nf</code> 41
. 99, 114,	<code>\tl_set:Nn</code> 102, 103,
116, 135, 146, 154, 166, 168, 170, 202	108, 109, 123, 127, 131, 142, 187, 233
<code>\ProcessOptions</code> 399	<code>\tl_set_eq:NN</code> 225, 226
<code>\prop_gput:Nnn</code> 37	<code>\tl_tail:f</code> 349
<code>\prop_if_in:NnF</code> 36	<code>\tl_to_str:n</code> 368
<code>\prop_map_inline:Nn</code> 266	U
<code>\prop_new:N</code> 9	<code>\usepackage</code> 11, 19, 52, 54
<code>\ProvidesExplPackage</code> 3	W
R	<code>\withargs:nn</code> 345, 374
<code>\regex_replace_all:nnN</code> 227	<code>\withargs:nnn</code> 320
<code>\relax</code> 399	<code>\withargs:nnnnn</code> 346
<code>\RenewDocumentCommand</code>	<code>\withargs:vvfvn</code> 330
. 52, 56, 60, 64, 68, 72, 358	<code>\withargs:xn</code> 329