

# The **skrapport** document class<sup>\*†</sup>

Simon Sigurdhsson [sigurdhsson@gmail.com]

Version 0.12d

**Abstract** A document class intended for simple documents *e.g.* reports handed in to courses and such. It is small, straightforward and heavily inspired by the Prac $\TeX$  Journal style.

## Contents

<b>1</b>	<b>Documentation</b>	<b>2</b>
1.1	Options . . . . .	2
	Layout [2] Style [3] Fonts [3] Functionality [4]	
1.2	User-level commands and environments . . . . .	5
	The front page [5] Sectioning [7] Macros and environments from article [8] Floats [9] Table of contents [9] Miscellaneous [10] Color theme support [10] Font size macros [10]	
1.3	Color themes . . . . .	12
<b>2</b>	<b>Known issues</b>	<b>13</b>
<b>3</b>	<b>Installation</b>	<b>14</b>
<b>4</b>	<b>Changes</b>	<b>14</b>
<b>5</b>	<b>Index</b>	<b>15</b>

---

\*Available on <http://www.ctan.org/pkg/skrapport>.

†Development version available on <https://github.com/urdh/skrapport>.

## 1 Documentation

The `skrapport` document class aims to make typesetting simple but stylish documents (mostly reports) as effortless as possible. It does this by mostly reimplementing the default article class in  $\LaTeX$ 3, while making modifications to both form and function along the way.

Because it is reimplemented in  $\LaTeX$ 3, it may be incompatible with any number of packages that patch or otherwise modify internals of article or other document classes. For commonly used packages (especially those used frequently by the author), this shouldn't be a problem. The author gladly accepts reports of any such issues at the project issue tracker — see 'Known issues' on page 13.

### 1.1 Options

As with other document classes, the class is loaded, possibly with options, by issuing `\documentclass [options] {skrapport}`. The class has a number of options controlling both form and function, by *e.g.* setting the font size, selecting a font stack, setting the section title style, and so on.

#### 1.1.1 Layout

Two options controlling the overall layout of the document are provided. Collectively they control the paper size and text layout of the document.

`paper`    `a4`, `a5` (`a4`)

The `paper` option controls the paper size of the document. Internally, this is set by the `typearea` package, so in theory many more paper sizes could be available, but the current options cover most useful documents.

`twocolumn`    The `twocolumn` option sets up a two-column mode. This is not provided by internal  $\LaTeX$  mechanics as in the original article class, but instead by patching environments and macros and using a combination of the `multicol` and `grid` packages. In theory, this means that baselines

of adjacent columns should be aligned, and that three- or four-column modes are possible in the future (but that'd be ridiculous).

### 1.1.2 Style

A couple of options to control the style of the document are provided. Two of them, `\leqno` and `\fleqn`, are mainly provided for compatibility with the `article` class.

`\leqno` This option makes display math environments typeset their labels on the left-hand side of the formula instead of the right-hand side.

`\fleqn` This option makes display math environments left-align the entire formula as opposed to centering it.

`indent` `true`, `false` (default) `false`

The `indent` option enables or disables the indentation of paragraphs, with the default being not to indent anything. The default behaviour thus is similar to that obtained using the `parskip` package with the `article` package.

`titles` `rm`, `it`, `bf`, `sf` (default) `bf`

Section titles (and a few other elements) are controlled by this option in that they are typeset either using the regular roman font, the boldfaced roman font or the sans serif font. For historical reasons the default is a boldfaced roman font, but the sans serif option is very handsome.

`hanging-titles` `true`, `false` (default) `false`

This options allow sections to be set as ‘hanging’ titles, *i.e.* with the section number in the margin.

`color` `<color theme>` (default) (default)

This option tells the class to activate color theme support and optionally load a color theme. Several color themes are available (as detailed by ‘Color themes’ on page 12), and the special value `false` disables color support entirely (which only means that the `xcolor` package isn’t loaded, and that `\colortheme` remains undefined).

### 1.1.3 Fonts

Only two options control the font setup of the document class. The class provides the same point sizes as `article`, but also provides a large number

of font stacks to choose from.

`ptsize` 10pt, 11pt, 12pt (11pt)  
 The document class provides the same three point sizes as the article class. There is room for expansion, but there really shouldn't be any reason to use other point sizes.

`font` none, kpfonts, lmodern, palatino, minion, skdoc, word  
 Several different font stacks, detailed by table 1 on the following page, are provided. Most of these work with pdf $\LaTeX$ , but there are two special font stacks: none and word. The former, predictably, loads no fonts whatsoever leaving the document with Computer Modern fonts. This is useful if the fonts are replaced later anyway, such as when using X $\LaTeX$ .

The word font stack, however, does load a few fonts. The fonts must be present and installed on the system as OTF or TTF fonts, and the font stack requires either X $\LaTeX$  or Lua $\LaTeX$ . Both word and none load the fontspec package, assuming the document is compiled using X $\LaTeX$  or Lua $\LaTeX$ .

*(Note: The skdoc font stack doesn't have a math font.)*

**Warning:** Currently, fontspec is always loaded by X $\LaTeX$  regardless of options due to the use of polyglossia. This means that you *have* to use OpenType fonts in your document, otherwise *only* Latin Modern Roman (*i.e.* no sans-serif or monospace fonts) will be available. Therefore, the word font stack is the default when using X $\LaTeX$ . Lua $\LaTeX$  is not affected by this.

#### 1.1.4 Functionality

The final three options affect functionality in one way or another. Since skrapport was originally designed for reports written in either swedish or english, the class always loads either babel or polyglossia with either of these languages. Additionally, the class may load the skmath package if desirable.

`nomath` true, false (false)  
 When false, the skmath package is loaded, providing improvements to the math functionality of amsmath and friends.

**Table 1:** *Font stacks provided by skrapport.*

Font stack	Serif font	Math font	Sans serif font	Monospace font
kpfonts	Kp-Fonts	Kp-Fonts	Kp-Fonts	Kp-Fonts
lmodern	Latin Modern	Latin Modern	Latin Modern	Source Code Pro
palatino	T <sub>E</sub> X Gyre	PX	Arev	Source Code Pro
minion	Minion Pro	Minion Pro	Myriad Pro	Source Code Pro
skdoc	PT Serif	—	Open Sans	Source Code Pro
word	Cambria	Cambria Math	Calibri	Consolas

- `lang` en, sv, de (sv)  
This option specifies what main language babel or polyglossia set up with. English (or swedish, for `lang=en`) is loaded as well, for use in constructs that allow for a second language.
- `draft` true, false (false)  
The draft option, much like in article, enables `\overfullrules` and possibly similar functionality in loaded packages (if they react to the global draft option).

## 1.2 User-level commands and environments

The general idea behind the document class is to provide most (if not all) of the macros provided by the standard L<sup>A</sup>T<sub>E</sub>X 2<sub>ε</sub> classes, as well as additional macros to simplify and beautify the documents produced. As such, most of the documentation that follows details macros that are present in the standard document classes. Some of them have changed functionality or semantics, so at least a skim through this section is recommended.

### 1.2.1 The front page

The front page is the part of the document that has seen the most changes in skrapport compared to article. In addition to the new, PracT<sub>E</sub>X-inspired layout, there are a few additional pieces of information in it. Also, the `\author` macro has been dramatically improved.

**\date** `{\ISO8601 date}`

The `\date` macro now internally employs `isodate` to typeset the date of the document. This means that the input must be either the string ‘today’, the token `\today` or a date as defined by ISO8601<sup>1</sup>. The mechanisms provided by `isodate` can be used to affect the output format.

**\author** `[\langle email \rangle]{\langle name \rangle}`

In contrast with the article package, the `\author` macro should no longer be used to typeset several author names at once. Instead, one `\author` command is to be issued for every author, optionally providing a corresponding email. These are then combined, in the order they are given, to form a list of authors and a corresponding list of email addresses.

**\regarding** `{\langle topic \rangle}`

This macro defines a topic or other short message detailing the purpose of the document. It is typeset along with the date in the upper left corner of the title page.

**\license** `{\langle license name \rangle}`

The `\license` macro defines a short license name to be typeset in the lower right corner of the title page. This mechanism could of course be used to typeset an institution name or similar as well. It is only typeset when also using the `titlepage` environment described below.

**\title** `{\langle document title \rangle}`

The `\title` macro, while not defined by `skrapport`, is relevant to describe. It simply sets the title of the document, as displayed by `\maketitle`.

**\maketitle** `[hide={date,regarding,email},nopdfinfo]`

As in article, the `\maketitle` macro typesets the information provided by `\title`, `\author` and friends to form a stylish front page. When

---

<sup>1</sup>International Organization for Standardization, Technical Committee 154 2004.

combined with `abstract`, `titlepage` and/or `\tableofcontents`, you get a very good-looking preamble with almost no effort.

The optional argument is a key-value list with two valid entries, `hide` and `nopdfinfo`. The `hide` entry accepts a comma-separated list in which the values `date`, `regarding` and `email` are interpreted as instructions to hide the corresponding entry from the front page. The `nopdfinfo` key disables the generation of PDF information by `hyperref`.

```
\begin{abstract}  
  <abstract text>  
\end{abstract}
```

The `abstract` environment defines an abstract, which is typeset in a block with the `\abstractname` word next to it (see e.g. the title page of this manual for an example).

```
\begin{titlepage}  
  <title page contents>  
\end{titlepage}
```

Normally, `\maketitle` doesn't reserve its own page. By enclosing `\maketitle` (and `abstract` if appropriate) in the `titlepage` environment, the contents are typeset on their own page, without page numbering and with the `\license` text in the lower right corner (if applicable).

### 1.2.2 Sectioning

```
\section    * [<short title>] {<title>}  
\subsection * [<short title>] {<title>}  
\subsubsection * [<short title>] {<title>}  
\paragraph  * [<short title>] {<title>}  
\subparagraph * [<short title>] {<title>}
```

The sectioning macros are superficially very similar to those provided by `article`, but have been completely reimplemented in `expl3` code. Additionally, the style of these sectioning macros, as detailed by the `titles` option documentation above, can be changed.

All of them have both arguments and behaviour in common, only differing in style. The starred versions are unnumbered, but still accept the optional short title (simply discarding it). The optional short title

is used in the table of contents. The `secnumdepth` counter limits the depth of section numbering.

The first three macros, being section titles, are typeset as actual titles on their own line with appropriate spacing above and below. The paragraph macros instead typeset run-in titles.

### 1.2.3 Macros and environments from article

Aside from the `itemize` and `enumerate` environments and the font selection macros, which are carried without modification from  $\text{\LaTeX} 2_{\epsilon}$ , a couple of environments and macros are defined.

The old font macros, whose use has been discouraged for a long time, are now deprecated. Instead of functioning correctly, they will emit an error and require user input. Use the `\text{??/}??family` macros instead. For emphasis, use the `\emph` macro.

`\emph` {*<text>*}

Emphasized text will be typeset in italic, or bold italic if the macro is used in a context where italic is already used (such as inside another `\emph` invocation).

`\begin{description}`

The `\begin{description}` environment behaves as expected, typesetting a list of descriptions as in the article class.

`\end{description}`

`\begin{quote}`

*<short quote>*

`\end{quote}`

Intended for short quotes, the `quote` environment simply typesets a centered block of italic text.

`\begin{quotation}`

*<long quote>*

`\end{quotation}`

Longer quoted passages are typeset using the `quotation` environment. This is simply a `quote` environment with additional spacing above and below.

`\begin{verse}`

*<pretentious poetry>*

`\end{verse}`

The `verse` environment is intended for poetry and other text where line breaks are critical. Use `\\` to break lines.



## **\appendix**

This macro signals the end of the main matter and the start of the appendix. In essence, it resets the section numbering counter and changes the section numbering to the upper-case alphabetic sequence.

### 1.2.4 Floats

Both the `figure` and `table` float environments accept an optional positioning argument. The default positioning is `tp`. Both environments also have starred variants, which do nothing in one-column mode while typesetting the figure across both columns in two-column mode. As usual, `\centering`, `\caption` and `\label` should be used inside the floats.

`\begin{figure}` [position]  
    `<content>`  
`\end{figure}` This float environment is intended for figures. The most common contents are `\includegraphics` statements or `tikzpicture` environments.

`\begin{table}` [position]  
    `<content>`  
`\end{table}` A float intended for tables. Probably contains `tabulars`.

`\begin{figcenter}`  
`\end{figcenter}` This environment is useful for wide figures and tables. It typesets its contents centered horizontally, but allows the content to extend into the margin. The content is set in a horizontal coffin.

### 1.2.5 Table of contents

## **\tableofcontents**

The table of contents are typeset using this macro. The `tocdepth` counter limits the depth of the table of contents, but for stylistic reasons values higher than 3 are unsupported.

### 1.2.6 Miscellaneous

**\comment** \*{\comment}  
**\note** \*{\comment}  
**\com** \*{\comment}

These macros, the two latter being aliases of the first one, typeset an author’s comment in the document. The starred variants typeset the comment inline with a red background, while the unstarred variant typesets the comment in a `\marginpar`.

**\eg**  
**\ie**  
**\etc**  
**\cf**  
**\viz**

These macro print the abbreviation of the latin phrases *exempli gratia*, *id est*, *et cetera*, *confer* and *videlicet*, respectively. The macros peek ahead to find punctuation marks and spaces, so they should behave correctly regardless of usage (assuming they’re used in running text and uncomplicated settings). In languages other than english, appropriate translations are made if applicable.

### 1.2.7 Color theme support

**\colortheme** {\theme}

The `\colortheme` macro, which is only available when the `color` option is `true`, applies a color theme to the document. For a list of available color themes, see ‘Color themes’ on page 12.

### 1.2.8 Font size macros

The font size macros, expectedly, set the size of the text. They do not take arguments, instead affecting all subsequent text of the current  $\TeX$

group, so use braces to provide and limit context. Also note that unlike article, these macros are *all* available, regardless of point size option.

**\tiny**

Typesets tiny text.

**\scriptsize**

Typesets script-size text.

**\footnotesize**

Typesets footnote-sized text.

**\small**

Typesets small text.

**\normalsize**

Typesets normal text.

**\large**

Typesets large text.

**\Large**

Typesets **slightly larger** text.

**\LARGE**

Typesets **even larger** text.

**\huge**

Typesets **huge** text.

## `\Huge`

Typesets **really huge** text.

### 1.3 Color themes

`\colortheme`  $\{ \langle theme \rangle \}$

If the package is loaded with the `color` option, changing the color theme is possible using `\colortheme`, which loads an appropriate package. At the moment, four color themes are available.

- `default` The default theme is fairly conservative, only coloring hyperref links with more readable, slightly darker colors than the standard ones. It should print well even on non-color printers.
- `unscathed` The unscathed theme is based on a palette with the same name on COLOURlovers<sup>2</sup>, and applies a dark brown color to emphasized text, a **rusty** color to links, a **darker rust** color to titles and a **lighter brown** to quotes.
- `cruelwater` The cruelwater theme is also based on a palette from COLOURlovers<sup>3</sup>, and applies a dark blue color to bold text and captions, a slightly less dark blue to titles and emphasized text, a **light gray** color to small print and a darker gray to quotes.
- `violet` The violet theme, like unscathed and cruelwater, is based on a COLOURlovers palette<sup>4</sup>. It colors all links **bright purple**, applies a dark puple color to titles, bold text and captions, a **grayish purple** to small print, a dark brown color to quotes and a **pastel violet** color to emphasized text.
- `skdoc` The skdoc theme is loosely based on the skdoc document class, with which this documentation is typeset.

---

<sup>2</sup><http://www.colourlovers.com/palette/1440498/unscathed>

<sup>3</sup>[http://www.colourlovers.com/palette/126030/Cruel\\_Water\\_at\\_Night](http://www.colourlovers.com/palette/126030/Cruel_Water_at_Night)

<sup>4</sup>[http://www.colourlovers.com/palette/1831303/Violet\\_White\\_Bedrm](http://www.colourlovers.com/palette/1831303/Violet_White_Bedrm)

## 2 Known issues

A list of current issues is available in the Github repository of this package<sup>5</sup>, but as of the release of v0.12d, there is one known issue:

- If a `\subsubsection` is the last item of the Table of Contents, it will not be indented properly.

If you discover any bugs in this package, please report them to the issue tracker in the skrapport Github repository.

---

<sup>5</sup><https://github.com/urdh/skrapport/issues>

### 3 Installation

The easiest way to install this package is using the package manager provided by your  $\TeX$  installation if such a program is available. Failing that, provided you have obtained the package source (`skrapport.tex` and `Makefile`) from either CTAN or Github, running `make install` inside the source directory works well. This will extract the documentation and code from `skrapport.tex`, install all files into the TDS tree at `TEXMFHOME` and run `mktexlsr`.

If you want to extract code and documentation without installing the package, run `make all` instead. If you insist on not using `make`, remember that packages distributed using `skdoc` must be extracted using `pdf $\LaTeX$` , *not* `tex` or `latex`.

### 4 Changes

v0.01

General: Initial version.

v0.03

General: Removed `\rd` and `\id`.

v0.04

General: Added `microtype` package.

v0.05

General: Improved documentation.

v0.06

General: Corrected checksum, further improved documentation.

v0.07

General: Various bugfixes,  $\Xe\TeX$  compatibility, better float settings, quote style fix, `intllimits` option to `amsmath`.

v0.07a

General: Fixed `kpfonts` issues.

v0.09

General: Introduced `kvoptions`, fixed abstract in `twocolumn` mode.

v0.10

General: Include `skmath` if exists and wanted. `Gobble` optional

	arguments to figure and table in two-column mode.	v0.12a	General: The fontspec package is now only loaded when using the word or none font stacks on Lua $\TeX$ or Xe $\TeX$ . The word font stack is now the default font stack on Xe $\TeX$ .
v0.10a	General: Include xparse (fixes breakage).		
v0.11	General: Added minion for Adobe Minion Pro font.	v0.12b	General: Minor and major bugfixes to \maketitle, ptsize, twocolumn and others.
v0.11a	General: Added skdoc font option and skdoc color theme.	v0.12c	General: Added german language option, fixed sectioning macros in twocolumn mode.
v0.12	General: Deprecated several macros, moved to $\LaTeX$ 3. Use of TOC depth above 3 is now unsupported.	v0.12d	General: Added hanging-titles, latin phrase macros. Load isomath. Don't load icomma. Use \frenchspacing.

## 5 Index

Numbers written in *italic* refer to the page where the corresponding entry is described; numbers underlined refer to the page where the implementation of the corresponding entry is discussed. Numbers in *roman* refer to other mentions of the entry.

A	<code>\abstractname</code> <i>7</i>
<code>abstract</code> (environment) <i>7</i>	<code>amsmath</code> (package) <i>4</i>

`\appendix` 9  
article (package) 2–8, 11  
`\author` 5, 6

**B**  
babel (package) 4, 5

**C**  
`\caption` 9  
`\centering` 9  
`\cf` 10  
color (option) 3, 10, 12  
`\colortheme` 3, 10, 12  
`\com` 10  
`\comment` 10  
cruelwater (theme) 12

**D**  
`\date` 6  
default (theme) 12  
description (environment) 8  
`\documentclass` 2  
draft (option) 5

**E**  
`\eg` 10  
`\emph` 8  
enumerate (environment) 8  
`\etc` 10  
expl3 (package) 7

**F**  
figcenter (environment) 9  
figure (environment) 9  
fleqn (option) 3

font (option) 4  
fontspec (package) 4  
`\footnotesize` 11

**G**  
grid (package) 2

**H**  
hanging-titles (option) 3  
`\Huge` 12  
`\huge` 11  
hyperref (package) 12  
hyperref (package) 7

**I**  
`\ie` 10  
`\includegraphics` 9  
indent (option) 3  
isodate (package) 6  
itemize (environment) 8

**L**  
`\label` 9  
lang (option) 5  
`\LARGE` 11  
`\Large` 11  
`\large` 11  
leqno (option) 3  
`\license` 6, 7

**M**  
Makefile (file) 14  
`\maketitle` 6, 7  
`\marginpar` 10  
multicol (package) 2



**N**  
 nomath (option) *4*  
 \normalsize *11*  
 \note *10*

**O**  
 \overfullrule *5*

**P**  
 paper (option) *2*  
 \paragraph *7*  
 parskip (package) *3*  
 polyglossia (package) *4, 5*  
 ptsize (option) *4*

**Q**  
 quotation (environment) *8*  
 quote (environment) *8*

**R**  
 \regarding *6*

**S**  
 \scriptsize *11*  
 \section *7*  
 skdoc (package) *12, 14*  
 skdoc (theme) *12*  
 skmath (package) *4*  
 skrapport (package) *6*  
 skrapport.tex (file) *14*  
 \small *11*  
 \subparagraph *7*  
 \subsection *7*  
 \subsubsection *7, 13*

**T**  
 table (environment) *9*  
 \tableofcontents *7, 9*  
 tabular (environment) *9*  
 tikzpicture (environment) *9*  
 \tiny *11*  
 \title *6*  
 titlepage (environment) *6, 7*  
 titles (option) *3, 7*  
 \today *6*  
 twocolumn (option) *2*  
 typearea (package) *2*

**U**  
 unscathed (theme) *12*

**V**  
 verse (environment) *8*  
 violet (theme) *12*  
 \viz *10*

**X**  
 xcolor (package) *3*

## 6 Bibliography

International Organization for Standardization, Technical Committee 154 (2004). *ISO 8601:2004. Data elements and interchange formats – Information interchange – Representation of dates and times.*